



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
0.375	■					0.049	0.277	0.171
	■					0.058	0.259	0.196
	■					0.065	0.245	0.215
	■		■			0.083	0.209	0.259
	■					0.095	0.185	0.284
	■					0.120	0.135	0.327
0.438	■					0.083	0.272	0.315
0.500	■					0.035	0.430	0.174
	■					0.049	0.402	0.236
	■					0.058	0.384	0.274
	■					0.065	0.370	0.302
	■					0.083	0.334	0.370
	■					0.095	0.310	0.411
	■					0.109	0.282	0.455
	■					0.120	0.260	0.487
	■		■			0.125	0.250	0.501
	■					0.134	0.232	0.524
	■					0.156	0.188	0.573
	■					0.188	0.125	0.626
	0.563	■					0.065	0.433
■						0.083	0.397	0.425
■						0.095	0.373	0.475
■								
0.625	■					0.035	0.555	0.221
	■					0.049	0.527	0.301
	■					0.058	0.509	0.351
	■					0.065	0.495	0.389
	■					0.083	0.459	0.480
	■					0.095	0.435	0.538
	■					0.109	0.407	0.601
	■					0.120	0.385	0.647
	■		■			0.125	0.375	0.668
	■					0.134	0.357	0.703
	■					0.156	0.313	0.781
	■					0.188	0.250	0.876
	0.688	■					0.065	0.558
■						0.083	0.522	0.536
■						0.095	0.498	0.602
■						0.120	0.448	0.728
■						0.134	0.420	0.793
■								
0.750	■					0.035	0.680	0.267
	■					0.049	0.652	0.367
	■					0.058	0.634	0.429
	■					0.065	0.620	0.476
	■					0.083	0.584	0.591
	■					0.095	0.560	0.665
	■		■			0.109	0.532	0.746
	■					0.120	0.510	0.807
	■					0.125	0.500	0.834
	■					0.134	0.482	0.882
	■		■			0.156	0.438	0.990
	■		■			0.188	0.375	1.126
	■					0.219	0.312	1.242
	■		■			0.250	0.250	1.335

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot	
0.813	■					0.065	0.683	0.519	
	■					0.083	0.647	0.647	
0.875	■					0.049	0.777	0.432	
	■					0.058	0.759	0.506	
	■					0.065	0.745	0.562	
	■					0.083	0.709	0.702	
	■					0.095	0.685	0.791	
	■					0.109	0.657	0.892	
	■					0.120	0.635	0.968	
	■					0.125	0.625	1.001	
	■					0.134	0.607	1.060	
0.938	■					0.095	0.748	0.855	
	■					0.120	0.697	1.048	
	■	■				0.134	0.670	1.151	
	■								
	1.000	■					0.049	0.902	0.498
		■					0.058	0.884	0.584
		■					0.065	0.870	0.649
		■					0.083	0.834	0.813
■						0.095	0.810	0.918	
■						0.109	0.782	1.037	
■						0.120	0.760	1.128	
■						0.125	0.750	1.168	
■						0.134	0.732	1.239	
■			■			0.156	0.688	1.406	
■						0.180	0.640	1.576	
■						0.188	0.625	1.627	
■						0.219	0.562	1.827	
1.063	■					0.250	0.500	2.003	
	■					0.281	0.438	2.158	
	■		■			0.313	0.375	2.295	
	■								
	■								

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot	Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
1.125	■					0.049	1.027	0.563	1.375	■					0.049	1.277	0.694
	■					0.058	1.009	0.661		■					0.065	1.245	0.909
	■					0.065	0.995	0.736		■					0.083	1.209	1.145
	■					0.083	0.959	0.924		■					0.095	1.185	1.299
	■					0.095	0.935	1.045		■					0.109	1.157	1.470
	■					0.109	0.907	1.183		■					0.120	1.135	1.608
	■					0.120	0.885	1.288		■					0.125	1.125	1.669
	■					0.125	0.875	1.335		■					0.134	1.107	1.776
	■					0.134	0.857	1.418		■					0.156	1.063	2.031
	■					0.156	0.813	1.614		■					0.188	1.000	2.378
	■		■			0.188	0.750	1.877		■	■				0.219	0.937	2.704
	■					0.219	0.687	2.119		■					0.250	0.875	3.004
	■					0.250	0.625	2.336		■					0.281	0.813	3.283
■					0.281	0.563	2.533	■					0.313	0.749	3.550		
1.188	■					0.065	1.058	0.780	1.500	■					0.049	1.402	0.759
	■					0.083	1.022	0.980		■					0.058	1.384	0.893
	■					0.095	0.998	1.109		■					0.065	1.370	0.996
	■					0.120	0.948	1.369		■					0.083	1.334	1.256
	■					0.125	0.938	1.419		■					0.095	1.310	1.426
	■					0.134	0.920	1.508		■					0.109	1.282	1.619
	■					0.156	0.876	1.719		■					0.120	1.260	1.769
	■					0.188	0.813	2.004		■					0.125	1.250	1.836
	■					0.219	0.750	2.266		■					0.134	1.232	1.955
	■					0.250	0.688	2.504		■					0.156	1.188	2.239
	■									■					0.188	1.125	2.628
1.250	■					0.049	1.152	0.629	■					0.219	1.062	2.996	
	■					0.065	1.120	0.823	■					0.250	1.000	3.338	
	■					0.083	1.084	1.034	■	■				0.281	0.938	3.658	
	■					0.095	1.060	1.172	■					0.313	0.875	3.963	
	■					0.109	1.032	1.328	■					0.344	0.812	4.247	
	■					0.120	1.010	1.448	■					0.375	0.750	4.506	
	■					0.125	1.000	1.502	■			■		0.500	0.500	5.340	
	■					0.134	0.982	1.597									
	■					0.156	0.938	1.823									
	■					0.188	0.875	2.128	1.563	■					0.065	1.433	1.040
	■					0.219	0.812	2.411		■					0.109	1.345	1.693
	■		■			0.250	0.750	2.670		■					0.120	1.323	1.849
	■					0.281	0.688	2.908		■					0.125	1.313	1.920
■			■		0.313	0.625	3.129	■						0.156	1.251	2.344	
■					0.375	0.500	3.504	■					0.250	1.063	3.506		
1.313	■					0.065	1.183	0.866	1.625	■					0.058	1.509	0.971
	■					0.083	1.147	1.090		■					0.065	1.495	1.083
	■					0.095	1.123	1.236		■					0.083	1.459	1.367
	■					0.109	1.095	1.402		■					0.095	1.435	1.552
	■					0.120	1.073	1.529		■					0.109	1.407	1.765
	■					0.134	1.045	1.687		■					0.120	1.385	1.929
	■					0.156	1.001	1.928		■					0.125	1.375	2.003
	■					0.188	0.938	2.254		■					0.134	1.357	2.134
	■		■			0.219	0.875	2.559		■					0.156	1.313	2.447
	■					0.250	0.813	2.838		■		■			0.188	1.250	2.879
	■					0.313	0.749	3.550		■		■			0.219	1.187	3.289
										■		■			0.250	1.125	3.671
										■		■			0.281	1.063	4.033
								■		■			0.313	1.000	4.380		
								■	■				0.375	0.875	5.006		



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
1.688	■					0.120	1.448	2.010
1.750	■					0.065	1.620	1.170
	■	■				0.083	1.584	1.478
	■					0.095	1.560	1.679
	■					0.109	1.532	1.910
	■					0.120	1.510	2.089
	■					0.125	1.500	2.169
	■					0.134	1.482	2.313
	■					0.156	1.438	2.656
	■					0.188	1.375	3.129
	■					0.219	1.312	3.581
	■					0.250	1.250	4.005
	■	■				0.281	1.188	4.409
	■					0.313	1.125	4.798
	■					0.375	1.000	5.507
			■		0.420	0.910	5.966	
			■		0.438	0.875	6.133	
			■		0.500	0.750	6.675	
1.768	■					0.250	1.268	4.053
1.875	■					0.065	1.745	1.257
	■					0.083	1.709	1.589
	■					0.095	1.685	1.806
	■					0.109	1.657	2.056
	■					0.120	1.635	2.249
	■					0.125	1.625	2.336
	■					0.134	1.607	2.492
	■					0.156	1.563	2.864
	■					0.188	1.500	3.379
	■	■				0.219	1.437	3.873
	■	■				0.250	1.375	4.339
	■	■				0.281	1.313	4.784
	■					0.313	1.250	5.215
	■					0.375	1.125	6.008
2.000	■					0.065	1.870	1.343
	■					0.083	1.834	1.699
	■					0.095	1.810	1.933
	■					0.109	1.782	2.201
	■					0.120	1.760	2.409
	■					0.125	1.750	2.503
	■					0.134	1.732	2.670
	■					0.156	1.688	3.072
	■					0.188	1.625	3.630
	■					0.219	1.562	4.166
	■					0.250	1.500	4.673
	■	■				0.281	1.438	5.159
	■	■				0.313	1.375	5.632
	■					0.344	1.312	6.084
■					0.375	1.250	6.508	
■			■		0.438	1.125	7.301	
■			■		0.500	1.000	8.010	
■					0.563	0.874	8.640	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
2.125	■					0.065	1.995	1.430
	■					0.083	1.959	1.810
	■					0.095	1.935	2.060
	■					0.109	1.907	2.347
	■					0.120	1.885	2.570
	■	■				0.125	1.875	2.670
	■					0.134	1.857	2.849
	■					0.156	1.813	3.281
	■					0.188	1.750	3.880
	■					0.219	1.687	4.458
	■					0.250	1.625	5.006
	■					0.281	1.563	5.534
	■	■				0.313	1.500	6.049
	■	■				0.344	1.437	6.543
■	■				0.375	1.375	7.009	
■					0.438	1.249	7.892	
■					0.500	1.125	8.678	
2.250	■					0.065	2.120	1.517
	■					0.083	2.084	1.921
	■					0.095	2.060	2.186
	■					0.109	2.032	2.492
	■					0.120	2.010	2.730
	■					0.125	2.000	2.837
	■					0.134	1.982	3.028
	■					0.156	1.938	3.489
	■					0.188	1.875	4.130
	■					0.219	1.812	4.750
	■					0.250	1.750	5.340
	■	■				0.281	1.688	5.909
	■	■				0.313	1.625	6.466
	■	■				0.344	1.562	7.002
■	■				0.375	1.500	7.509	
■	■				0.438	1.375	8.469	
■	■		■		0.500	1.250	9.345	
■	■				0.531	1.188	9.749	
■	■				0.563	1.125	10.138	
2.375	■					0.065	2.245	1.604
	■					0.083	2.209	2.032
	■					0.095	2.185	2.313
	■					0.109	2.157	2.638
	■					0.120	2.135	2.890
	■					0.125	2.125	3.004
	■					0.134	2.107	3.207
	■					0.156	2.063	3.697
	■					0.188	2.000	4.380
	■	■				0.219	1.937	5.043
	■					0.250	1.875	5.674
	■					0.281	1.813	6.284
	■	■				0.313	1.750	6.884
	■	■				0.344	1.687	7.462
■					0.375	1.625	8.010	
■					0.438	1.500	9.053	
■	■				0.500	1.375	10.013	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
2.438		■				0.281	1.876	6.473
2.500	■					0.065	2.370	1.690
	■					0.083	2.334	2.143
	■					0.095	2.310	2.440
	■					0.109	2.282	2.783
	■					0.120	2.260	3.050
	■					0.125	2.250	3.171
	■					0.134	2.232	3.386
	■					0.156	2.188	3.905
	■					0.188	2.125	4.631
	■					0.219	2.062	5.335
	■	■				0.250	2.000	6.008
	■	■				0.281	1.938	6.659
	■	■				0.313	1.875	7.301
	■					0.344	1.812	7.921
	■					0.375	1.750	8.511
	■	■				0.406	1.688	9.080
	■	■				0.438	1.625	9.637
	■	■	■			0.500	1.500	10.680
	■	■				0.563	1.375	11.640
	■					0.625	1.250	12.516
	■		■			0.750	1.000	14.018
2.563	■					0.188	2.188	4.757
2.625	■					0.065	2.495	1.777
	■					0.083	2.459	2.253
	■					0.095	2.435	2.567
	■					0.109	2.407	2.929
	■					0.120	2.385	3.210
	■					0.125	2.375	3.338
	■					0.134	2.357	3.565
	■					0.156	2.313	4.114
	■	■				0.188	2.250	4.881
	■					0.219	2.187	5.627
	■	■				0.250	2.125	6.341
	■					0.281	2.063	7.035
	■	■				0.313	2.000	7.718
	■	■				0.344	1.937	8.380
	■	■				0.375	1.875	9.011
	■					0.438	1.750	10.221
	■					0.500	1.625	11.348
	■					0.625	1.375	13.350

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
2.750	■					0.065	2.620	1.864
	■					0.083	2.584	2.364
	■					0.095	2.560	2.694
	■					0.109	2.532	3.074
	■					0.120	2.510	3.371
	■					0.125	2.500	3.504
	■					0.134	2.482	3.744
	■					0.156	2.438	4.322
	■					0.188	2.375	5.131
	■					0.219	2.312	5.920
	■	■				0.250	2.250	6.675
	■	■				0.281	2.188	7.410
	■	■				0.313	2.125	8.135
	■	■				0.344	2.062	8.839
	■					0.360	2.030	9.189
	■	■				0.375	2.000	9.512
	■	■				0.438	1.875	10.805
	■	■				0.500	1.750	12.015
	■	■				0.563	1.625	13.141
	■	■	■			0.625	1.500	14.184
2.875	■					0.065	2.745	1.951
	■					0.083	2.709	2.475
	■					0.095	2.685	2.821
	■					0.120	2.635	3.531
	■					0.125	2.625	3.671
	■					0.134	2.607	3.923
	■					0.156	2.563	4.530
	■					0.188	2.500	5.382
	■					0.219	2.437	6.212
	■					0.250	2.375	7.009
	■					0.281	2.313	7.785
	■	■				0.313	2.250	8.552
	■	■				0.375	2.125	10.013
	■	■				0.438	2.000	11.389
	■	■				0.500	1.875	12.683
				■		0.750	1.375	17.021



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
3.000	■					0.065	2.870	2.037
	■					0.083	2.834	2.586
	■					0.095	2.810	2.947
	■					0.109	2.782	3.365
	■					0.120	2.760	3.691
	■					0.125	2.750	3.838
	■					0.134	2.732	4.102
	■					0.156	2.688	4.738
	■					0.188	2.625	5.632
	■					0.219	2.562	6.505
	■					0.250	2.500	7.343
	■					0.281	2.438	8.160
	■	■				0.313	2.375	8.970
	■					0.344	2.312	9.758
	■					0.375	2.250	10.513
	■					0.438	2.125	11.973
	■				■	0.500	2.000	13.350
	■				■	0.563	1.875	14.643
	■					0.625	1.750	15.853
	■			■		0.688	1.624	16.988
■			■	■	0.750	1.500	18.023	
■			■	■	0.875	1.250	19.858	
■			■	■	1.000	1.000	21.360	

3.063	■					0.313	2.437	9.400
--------------	---	--	--	--	--	-------	-------	-------

3.125	■					0.065	2.995	2.124
	■					0.083	2.959	2.697
	■					0.095	2.935	3.074
	■					0.109	2.907	3.511
	■					0.120	2.885	3.851
	■					0.125	2.875	4.005
	■					0.134	2.857	4.280
	■					0.156	2.813	4.947
	■					0.188	2.750	5.882
	■					0.219	2.687	6.797
	■					0.250	2.625	7.676
	■					0.281	2.563	8.535
	■					0.313	2.500	9.387
	■	■				0.344	2.437	10.217
	■					0.375	2.375	11.014
	■	■				0.438	2.250	12.557
	■					0.500	2.125	14.018
	■					0.563	2.000	15.394
	■					0.625	1.875	16.688
	■			■		0.750	1.625	19.024

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
3.250	■					0.065	3.120	2.211
	■					0.083	3.084	2.807
	■					0.095	3.060	3.201
	■					0.120	3.010	4.011
	■					0.125	3.000	4.172
	■					0.134	2.982	4.459
	■					0.156	2.938	5.155
	■					0.188	2.875	6.133
	■					0.219	2.812	7.089
	■		■			0.250	2.750	8.010
	■		■			0.281	2.688	8.910
	■		■			0.313	2.625	9.804
	■					0.344	2.562	10.676
	■					0.375	2.500	11.514
	■					0.406	2.438	12.332
	■		■			0.438	2.375	13.141
	■		■			0.500	2.250	14.685
	■		■			0.563	2.125	16.145
	■		■		■	0.625	2.000	17.522
	■			■	■	0.750	1.750	20.025
■			■	■	0.875	1.500	22.194	
■			■	■	1.000	1.250	24.030	

3.375	■					0.120	3.135	4.172
	■					0.125	3.125	4.339
	■					0.134	3.107	4.638
	■					0.156	3.063	5.363
	■					0.188	3.000	6.383
	■					0.208	2.959	7.035
	■					0.250	2.875	8.344
	■					0.313	2.750	10.221
	■		■			0.375	2.625	12.015
	■		■			0.500	2.375	15.353
■				■	0.625	2.125	18.356	

3.500	■					0.065	3.370	2.385
	■					0.083	3.334	3.029
	■					0.095	3.310	3.455
	■					0.109	3.282	3.948
	■					0.120	3.260	4.332
	■					0.125	3.250	4.506
	■					0.134	3.232	4.817
	■					0.156	3.188	5.571
	■					0.188	3.125	6.633
	■					0.219	3.062	7.674
	■					0.250	3.000	8.678
	■					0.281	2.938	9.660
	■					0.313	2.875	10.638
	■		■			0.375	2.750	12.516
	■		■			0.438	2.625	14.310
	■				■	0.500	2.500	16.020
	■					0.625	2.250	19.191
	■			■	■	0.750	2.000	22.028
	■			■	■	0.875	1.750	24.531
	■			■	■	1.000	1.500	26.700

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
3.555	■					0.207	3.141	7.556
3.625	■					0.125	3.375	4.673
	■					0.188	3.250	6.884
	■					0.250	3.125	9.011
	■					0.313	3.000	11.055
	■	■				0.375	2.875	13.016
3.688		■				0.422	2.844	14.720
		■						
3.750	■					0.095	3.560	3.708
	■					0.125	3.500	4.839
	■					0.188	3.375	7.134
	■					0.219	3.312	8.259
	■					0.250	3.250	9.345
	■					0.313	3.125	11.473
	■					0.375	3.000	13.517
	■	■				0.438	2.875	15.478
	■	■		■		0.500	2.750	17.355
	■	■				0.563	2.625	19.149
3.875	■					0.625	2.500	20.859
	■		■		■	0.750	2.250	24.030
	■		■	■	■	0.875	2.000	26.867
	■		■	■	■	1.000	1.750	29.370
	■							
4.000	■					0.188	3.500	7.384
	■					0.250	3.375	9.679
	■					0.313	3.250	11.890
	■					0.375	3.125	14.018
	■	■				0.406	3.063	15.042
	■	■				0.438	3.000	16.062
	■	■				0.500	2.875	18.023
	■	■				0.625	2.625	21.694
4.000	■		■			0.750	2.375	25.031
	■					0.065	3.870	2.732
	■					0.083	3.834	3.472
	■					0.095	3.810	3.962
	■					0.109	3.782	4.530
	■					0.120	3.760	4.973
	■					0.125	3.750	5.173
	■					0.134	3.732	5.533
	■					0.156	3.688	6.404
	■					0.188	3.625	7.635
	■					0.219	3.562	8.843
	■					0.250	3.500	10.013
	■					0.281	3.438	11.161
	■					0.313	3.375	12.307
	■					0.375	3.250	14.518
■					0.438	3.125	16.646	
■			■	■	0.500	3.000	18.690	
■			■	■	0.563	2.875	20.651	
■			■	■	0.625	2.750	22.528	
■		■	■	■	0.750	2.500	26.033	
■		■	■	■	0.875	2.250	29.203	
■		■	■	■	1.000	2.000	32.040	
■		■	■	■	1.250	1.500	36.713	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
4.022		■				0.511	3.000	19.560
4.062		■				0.284	3.494	11.559
4.095	■					0.180	3.735	7.526
4.125	■					0.188	3.750	7.885
	■					0.250	3.625	10.346
	■					0.313	3.500	12.724
	■	■				0.375	3.375	15.019
	■	■				0.500	3.125	19.358
	■	■				0.563	3.000	21.402
4.250	■	■				0.625	2.875	23.363
	■					0.095	4.060	4.216
	■					0.120	4.010	5.293
	■					0.125	4.000	5.507
	■					0.134	3.982	5.890
	■					0.156	3.938	6.821
	■					0.188	3.875	8.135
	■					0.250	3.750	10.680
	■					0.313	3.625	13.141
	■					0.375	3.500	15.519
4.375	■			■	■	0.500	3.250	20.025
	■			■	■	0.563	3.124	22.169
	■			■	■	0.625	3.000	24.197
	■		■	■	■	0.688	2.874	26.173
	■		■	■	■	0.750	2.750	28.035
	■		■	■	■	0.875	2.500	31.539
4.375	■				■	1.000	2.250	34.710
	■				■	1.250	1.750	40.050
	■					0.188	4.000	8.385
	■					0.250	3.875	11.014
	■					0.313	3.750	13.559
	■					0.375	3.625	16.020
	■	■				0.438	3.500	18.398
4.375	■	■				0.500	3.375	20.693
	■		■			0.688	2.999	27.091
	■							



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot	
4.500	■					0.095	4.310	4.469	
	■					0.125	4.250	5.841	
	■					0.134	4.232	6.248	
	■					0.156	4.188	7.237	
	■					0.188	4.125	8.636	
	■	■				0.219	4.062	10.013	
	■					0.250	4.000	11.348	
	■					0.259	3.982	11.731	
	■					0.281	3.938	12.662	
	■	■				0.313	3.875	13.976	
	■					0.340	3.820	15.106	
	■					0.375	3.750	16.521	
	■					0.438	3.625	18.982	
	■			■	■	0.500	3.500	21.360	
	■					0.563	3.375	23.655	
	■					0.625	3.250	25.866	
	4.562	■					0.165	4.232	7.748
4.593		■				0.180	4.233	8.484	
		4.625	■				0.188	4.250	8.886
			■				0.250	4.125	11.681
			■				0.313	4.000	14.393
■					0.375	3.875	17.021		
■				■		0.500	3.625	22.028	
■					0.625	3.375	26.700		
4.750	■					0.120	4.510	5.934	
	■					0.125	4.500	6.174	
	■					0.188	4.375	9.136	
	■					0.250	4.250	12.015	
	■					0.313	4.125	14.810	
	■					0.375	4.000	17.522	
	■					0.438	3.875	20.150	
	■					0.500	3.750	22.695	
	■					0.625	3.500	27.534	
	■			■	■	0.750	3.250	32.040	
	■			■		0.812	3.126	34.151	
	■					0.875	3.000	36.212	
	■			■	■	1.000	2.750	40.050	
	■					1.250	2.250	46.725	
■					1.500	1.750	52.065		

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot	
5.000	■					0.083	4.834	4.359	
	■					0.120	4.760	6.254	
	■					0.125	4.750	6.508	
	■					0.188	4.625	9.637	
	■					0.250	4.500	12.683	
	■	■				0.313	4.375	15.645	
	■					0.375	4.250	18.523	
	■				■	0.394	4.212	19.382	
	■					0.438	4.125	21.318	
	■				■	0.500	4.000	24.030	
	■			■	■	0.563	3.875	26.658	
	■				■	0.625	3.750	29.203	
	■			■	■	0.750	3.500	34.043	
	■			■	■	0.875	3.250	38.548	
5.125	■					0.313	4.500	16.062	
	■	■				0.500	4.125	24.698	
	5.250	■					0.120	5.010	6.575
		■					0.125	5.000	6.842
■						0.188	4.875	10.138	
■						0.250	4.750	13.350	
■						0.313	4.625	16.479	
■						0.375	4.500	19.524	
■		■			■	0.500	4.250	25.365	
■				■	■	0.625	4.000	30.872	
5.500	■					0.120	5.260	6.895	
	■					0.188	5.125	10.638	
	■					0.250	5.000	14.018	
	■					0.313	4.875	17.313	
	■	■				0.375	4.750	20.526	
	■				■	0.500	4.500	26.700	
5.563	■					0.250	5.063	14.186	
	5.625	■					0.313	5.000	17.760

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
5.750	■					0.250	5.250	14.685
	■					0.313	5.125	18.148
	■					0.375	5.000	21.527
	■			■		0.500	4.750	28.035
	■					0.625	4.500	34.209
			■			0.750	4.250	40.050
				■	■	0.875	4.000	45.557
			■	■	■	1.000	3.750	50.730
				■	■	1.125	3.500	55.569
				■	■	1.250	3.250	60.075
				■	1.500	2.750	68.085	
5.906					■	0.591	4.724	34.141
6.000	■					0.083	5.834	5.245
	■					0.120	5.760	7.536
	■					0.125	5.750	7.843
	■					0.188	5.625	11.640
	■					0.250	5.500	15.353
	■					0.313	5.375	18.982
	■					0.375	5.250	22.528
	■			■	■	0.500	5.000	29.370
	■			■	■	0.625	4.750	35.878
			■	■	■	0.750	4.500	42.053
			■	■	■	0.875	4.250	47.893
			■	■	■	1.000	4.000	53.400
				■	■	1.250	3.500	63.413
			■	■	1.500	3.000	72.090	
			■	■	1.750	2.500	79.433	
			■	■	2.000	2.000	85.440	
6.250	■					0.120	6.010	7.856
	■					0.125	6.000	8.177
	■					0.134	5.982	8.753
	■					0.188	5.875	12.140
	■					0.250	5.750	16.020
	■					0.375	5.500	23.529
	■			■	■	0.500	5.250	30.705
	■			■	■	0.625	5.000	37.547
			■	■	■	0.750	4.750	44.055
			■	■	■	1.000	4.250	56.070
			■	■	1.250	3.750	66.750	
			■	■	1.500	3.250	76.095	
6.500	■	■				0.250	6.000	16.688
	■					0.375	5.750	24.531
	■				■	0.500	5.500	32.040
	■					0.625	5.250	39.216
			■	■	■	0.750	5.000	46.058
			■	■	■	1.000	4.500	58.740
				■	■	1.250	4.000	70.088
				■	■	1.375	3.750	75.261
				■	■	1.500	3.500	80.100
					■	1.750	3.000	88.778
				■	■	1.875	2.750	92.616
				■	■	2.000	2.500	96.120

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
6.625	■					0.313	6.000	21.068
					■	0.432	5.761	28.573
					■	0.563	5.499	36.450
					■	0.719	5.187	45.352
					■	0.864	4.897	53.160
6.750	■					0.250	6.250	17.355
	■					0.375	6.000	25.532
	■					0.500	5.750	33.375
	■				■	0.625	5.500	40.884
					■	0.750	5.250	48.060
					■	0.875	5.000	54.902
			■	■	■	1.000	4.750	61.410
				■	■	1.250	4.250	73.425
				■	■	1.500	3.750	84.105
				■	■	1.625	3.500	88.944
7.000	■					0.188	6.625	13.642
	■					0.250	6.500	18.023
	■					0.375	6.250	26.533
	■				■	0.500	6.000	34.710
	■	■			■	0.625	5.750	42.553
			■	■	■	0.750	5.500	50.063
			■	■	■	1.000	5.000	64.080
				■	■	1.250	4.500	76.763
				■	■	1.500	4.000	88.110
				■	■	1.750	3.500	98.123
				■	2.000	3.000	106.800	
7.087					■	0.394	6.299	28.849
7.250	■					0.250	6.750	18.690
	■					0.375	6.500	27.534
	■				■	0.500	6.250	36.045
	■				■	0.625	6.000	44.222
				■	■	0.750	5.750	52.065
				■	■	1.000	5.250	66.750
			■	■	1.250	4.750	80.100	
			■	■	1.500	4.250	92.115	
7.500	■					0.250	7.000	19.358
	■					0.375	6.750	28.536
	■				■	0.500	6.500	37.380
	■				■	0.625	6.250	45.891
			■	■	■	0.750	6.000	54.068
			■	■	■	0.875	5.750	61.911
			■	■	■	1.000	5.500	69.420
				■	■	1.125	5.250	76.596
				■	■	1.250	5.000	83.438
				■	■	1.500	4.500	96.120
			■	■	1.750	4.000	107.468	
				■	2.000	3.500	117.480	
7.625					■	0.500	6.625	38.048
					■	0.750	6.125	55.069
					■	0.787	6.051	57.474
					■	1.000	5.625	70.755



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
7.750	■					0.250	7.250	20.025
	■					0.375	7.000	29.537
	■				■	0.500	6.750	38.715
					■	0.750	6.250	56.070
			■	■	■	1.000	5.750	72.090
					■	1.250	5.250	86.775
					■	1.500	4.750	100.125
					■	1.750	4.250	112.140
8.000	■					0.250	7.500	20.693
	■				■	0.375	7.250	30.538
	■				■	0.500	7.000	40.050
	■	■			■	0.625	6.750	49.228
			■	■	■	0.750	6.500	58.073
			■	■	■	1.000	6.000	74.760
				■	■	1.250	5.500	90.113
				■	■	1.500	5.000	104.130
				■	■	1.750	4.500	116.813
				■	■	2.000	4.000	128.160
					■	2.250	3.500	138.173
					■	2.500	3.000	146.850
8.250	■					0.250	7.750	21.360
	■					0.375	7.500	31.539
	■				■	0.500	7.250	41.385
	■					0.625	7.000	50.897
					■	0.750	6.750	60.075
				■	■	1.000	6.250	77.430
				■	■	1.250	5.750	93.450
				■	■	1.500	5.250	108.135
				■	2.000	4.250	133.500	
8.500	■					0.250	8.000	22.028
	■	■				0.375	7.750	32.541
	■				■	0.500	7.500	42.720
	■					0.625	7.250	52.566
				■	■	0.750	7.000	62.078
			■	■	■	1.000	6.500	80.100
				■	■	1.125	6.250	88.611
				■	■	1.250	6.000	96.788
				■	■	1.500	5.500	112.140
				■	■	1.750	5.000	126.158
				■	■	2.000	4.500	138.840
				■		2.250	4.000	150.188
				■	2.500	3.500	160.200	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
8.625					■	0.394	7.837	34.635
					■	0.500	7.625	43.388
					■	0.594	7.437	50.948
					■	0.719	7.187	60.710
					■	0.812	7.001	67.756
					■	0.875	6.875	72.424
					■	0.906	6.813	74.690
					■	1.000	6.625	81.435
					■	1.250	6.125	98.456
					■	1.500	5.625	114.143
8.750	■					0.375	8.000	33.542
	■					0.500	7.750	44.055
					■	0.750	7.250	64.080
			■		■	1.000	6.750	82.770
					■	1.250	6.250	100.125
					■	1.375	6.000	108.302
					■	1.500	5.750	116.145
					■	2.000	4.750	144.180
9.000	■					0.250	8.500	23.363
	■					0.375	8.250	34.543
	■	■			■	0.500	8.000	45.390
	■					0.625	7.750	55.903
			■	■	■	0.750	7.500	66.083
				■	■	1.000	7.000	85.440
				■	■	1.250	6.500	103.463
				■	■	1.500	6.000	120.150
				■	■	1.750	5.500	135.503
				■	■	2.000	5.000	149.520
				■	2.500	4.000	173.550	
				■	3.000	3.000	192.240	
9.250	■					0.250	8.750	24.030
	■					0.375	8.500	35.544
	■					0.500	8.250	46.725
					■	0.750	7.750	68.085
				■	■	1.000	7.250	88.110
				■		1.125	7.000	97.622
					■	1.250	6.750	106.800
					■	1.500	6.250	124.155
				■	■	2.000	5.250	154.860
					■	2.500	4.250	180.225
9.500	■					0.250	9.000	24.698
	■					0.375	8.750	36.546
	■				■	0.500	8.500	48.060
	■					0.625	8.250	59.241
					■	0.750	8.000	70.088
					■	0.875	7.750	80.601
					■	1.000	7.500	90.780
					■	1.250	7.000	110.138
					■	1.500	6.500	128.160
					■	1.750	6.000	144.848
				■	2.000	5.500	160.200	
				■	2.250	5.000	174.218	
				■	2.500	4.500	186.900	

DOM Welded and Drawn Over Mandrel Carbon Steel Tubing ASTM A-513/5
 < .156 Walls C1020
 ≥ .156 Walls C1026

ST52.3 Welded and Drawn Over Mandrel Carbon Steel Tubing ASTM A-513/5

CDS Cold Drawn Seamless Carbon Steel Tubing ASTM A-519

ALY Hot Finished Seamless Alloy 4140/42 Alloy Steel Tubing, Annealed, ASTM A-519

HFS Hot Finished Seamless C1026 Carbon Mechanical Tubing ASTM A-519

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
9.625					■	0.472	8.681	46.140
9.750	■					0.250	9.250	25.365
	■				■	0.375	9.000	37.547
	■				■	0.500	8.750	49.395
					■	0.750	8.250	72.090
					■	1.000	7.750	93.450
					■	1.130	7.490	104.030
					■	1.250	7.250	113.475
					■	1.500	6.750	132.165
10.000	■					0.250	9.500	26.033
	■					0.375	9.250	38.548
	■				■	0.500	9.000	50.730
			■	■	■	0.750	8.500	74.093
			■	■	■	1.000	8.000	96.120
				■	■	1.125	7.750	106.633
				■	■	1.250	7.500	116.813
				■	■	1.500	7.000	136.170
				■	■	1.750	6.500	154.193
				■	■	2.000	6.000	170.880
					■	2.250	5.500	186.233
				■	■	2.500	5.000	200.250
					■	3.000	4.000	224.280
10.188	■					0.375	9.438	39.549
10.250	■					0.250	9.750	26.700
	■					0.375	9.500	39.549
	■					0.500	9.250	52.065
					■	0.750	8.750	76.095
					■	1.000	8.250	98.790
					■	1.250	7.750	120.150
					■	1.500	7.250	140.175
					■	2.000	6.250	176.220
					■	2.250	5.750	192.240
					■	2.500	5.250	206.925
10.500	■					0.250	10.000	27.368
	■					0.375	9.750	40.551
	■				■	0.500	9.500	53.400
					■	0.750	9.000	78.098
				■	■	1.000	8.500	101.460
				■	■	1.250	8.000	123.488
				■	■	1.500	7.500	144.180
				■	■	1.750	7.000	163.538
				■	■	2.000	6.500	181.560
				■	■	2.250	6.000	198.248
					■	2.500	5.500	213.600
					■	3.000	4.500	240.300

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
10.750	■					0.250	10.250	28.035
	■					0.375	10.000	41.552
	■					0.500	9.750	54.735
					■	0.594	9.562	64.429
					■	0.719	9.312	77.027
					■	0.750	9.250	80.100
					■	0.844	9.062	89.292
				■	■	1.000	8.750	104.130
				■	■	1.125	8.500	115.644
				■	■	1.250	8.250	126.825
				■	■	1.500	7.750	148.185
					■	1.750	7.250	168.210
					■	2.000	6.750	186.900
					■	2.500	5.750	220.275
11.000	■					0.250	10.500	28.703
	■					0.375	10.250	42.553
	■					0.500	10.000	56.070
					■	0.750	9.500	82.103
					■	1.000	9.000	106.800
					■	1.250	8.500	130.163
					■	1.500	8.000	152.190
					■	1.750	7.500	172.883
					■	2.000	7.000	192.240
					■	2.250	6.500	210.263
					■	2.500	6.000	226.950
					■	3.000	5.000	256.320
11.250					■	0.750	9.750	84.105
					■	1.000	9.250	109.470
					■	1.250	8.750	133.500
					■	1.500	8.250	156.195
					■	2.000	7.250	197.580
11.500	■					0.375	10.750	44.556
	■					0.500	10.500	58.740
					■	0.750	10.000	86.108
					■	1.000	9.500	112.140
				■	■	1.250	9.000	136.838
				■	■	1.500	8.500	160.200
					■	1.750	8.000	182.228
				■	■	2.000	7.500	202.920
					■	2.250	7.000	222.278
					■	2.500	6.500	240.300
11.750					■	0.591	10.568	70.434
					■	0.750	10.250	88.110
					■	1.000	9.750	114.810
					■	1.250	9.250	140.175
					■	1.500	8.750	164.205
					■	1.750	8.250	186.900
					■	2.000	7.750	208.260
					■	2.500	6.750	246.975



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
12.000	■					0.250	11.500	31.373
	■					0.375	11.250	46.558
	■					0.500	11.000	61.410
				■	■	0.750	10.500	90.113
				■	■	1.000	10.000	117.480
				■	■	1.250	9.500	143.513
				■	■	1.500	9.000	168.210
				■	■	1.750	8.500	191.573
					■	2.000	8.000	213.600
				■	■	2.250	7.500	234.293
			■	■	2.500	7.000	253.650	
			■	■	3.000	6.000	288.360	
12.250					■	0.750	10.750	92.115
					■	1.000	10.250	120.150
					■	1.250	9.750	146.850
					■	1.500	9.250	172.215
					■	2.000	8.250	218.940
12.500	■				■	0.500	11.500	64.080
				■	■	0.750	11.000	94.118
				■	■	1.000	10.500	122.820
				■	■	1.250	10.000	150.188
				■	■	1.500	9.500	176.220
				■	■	1.750	9.000	200.918
				■	■	2.000	8.500	224.280
				■	2.250	8.000	246.308	
			■	■	2.500	7.500	267.000	
12.750					■	0.688	11.375	88.569
					■	0.750	11.250	96.120
					■	0.844	11.062	107.320
					■	1.000	10.750	125.490
					■	1.125	10.500	139.674
					■	1.250	10.250	153.525
					■	1.313	10.125	160.325
					■	1.500	9.750	180.225
					■	1.750	9.250	205.590
					■	2.000	8.750	229.620
				■	2.500	7.750	273.675	
13.000	■					0.250	12.500	34.040
					■	0.500	12.000	66.750
					■	0.750	11.500	98.123
				■	■	1.000	11.000	128.160
				■	■	1.250	10.500	156.863
				■	■	1.500	10.000	184.230
					■	1.750	9.500	210.263
				■	■	2.000	9.000	234.960
				■	■	2.500	8.000	280.350
				■	3.000	7.000	320.400	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
13.375					■	0.500	12.375	68.753
					■	0.750	11.875	101.126
					■	1.000	11.375	132.165
					■	1.250	10.875	161.869
					■	1.500	10.375	190.238
					■	2.000	9.375	242.970
				■	2.500	8.375	290.363	
14.000					■	0.500	13.000	72.090
				■	■	0.750	12.500	106.133
				■	■	0.938	12.124	130.853
				■	■	1.000	12.000	138.840
					■	1.093	11.814	150.667
					■	1.250	11.500	170.213
					■	1.406	11.188	189.113
				■	■	1.500	11.000	200.250
				■	■	1.750	10.500	228.953
				■	■	2.000	10.000	256.320
				■	2.250	9.500	282.353	
			■	■	2.500	9.000	307.050	
			■	■	3.000	8.000	352.440	
			■	■	3.500	7.000	392.490	
14.375					■	0.750	12.875	109.136
					■	1.000	12.375	142.845
					■	1.250	11.875	175.219
					■	1.500	11.375	206.258
					■	1.750	10.875	235.961
					■	2.000	10.375	264.330
					■	2.500	9.375	317.063
				■	■	3.000	8.375	364.455
14.750					■	0.750	13.250	112.140
15.000					■	0.500	14.000	77.430
					■	0.750	13.500	114.143
				■	■	1.000	13.000	149.520
				■	■	1.250	12.500	183.563
				■	■	1.500	12.000	216.270
				■	■	1.750	11.500	247.643
				■	■	2.000	11.000	277.680
				■	■	2.250	10.500	306.383
			■	■	2.500	10.000	333.750	
			■	■	3.000	9.000	384.480	
15.500					■	0.500	14.500	80.100
					■	0.750	14.000	118.148
					■	1.000	13.500	154.860
					■	1.250	13.000	190.238
					■	1.500	12.500	224.280
					■	1.750	12.000	256.988
					■	2.000	11.500	288.360
					■	2.500	10.500	347.100

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
16.000					■	0.500	15.000	82.770
					■	0.656	14.688	107.501
					■	0.750	14.500	122.153
					■	0.844	14.312	136.615
				■	■	1.000	14.000	160.200
					■	1.031	13.938	164.825
					■	1.219	13.562	192.433
					■	1.250	13.500	196.913
					■	1.438	13.124	223.641
				■	■	1.500	13.000	232.290
					■	1.594	12.812	245.247
					■	1.750	12.500	266.333
				■	■	2.000	12.000	299.040
					■	2.250	11.500	330.413
				■	■	2.500	11.000	360.450
			■	■	3.000	10.000	416.520	
				■	3.500	9.000	467.250	
16.500					■	0.750	15.000	126.158
					■	1.000	14.500	165.540
					■	1.250	14.000	203.588
					■	1.500	13.500	240.300
					■	1.750	13.000	275.678
					■	2.000	12.500	309.720
				■	2.500	11.500	373.800	
17.000					■	0.500	16.000	88.110
					■	0.750	15.500	130.163
				■	■	1.000	15.000	170.880
					■	1.250	14.500	210.263
				■	■	1.500	14.000	248.310
					■	1.750	13.500	285.023
				■	■	2.000	13.000	320.400
				■	■	2.500	12.000	387.150
			■	■	3.000	11.000	448.560	
17.500					■	0.750	16.000	134.168
					■	1.000	15.500	176.220
					■	1.250	15.000	216.938
					■	1.500	14.500	256.320
					■	2.000	13.500	331.080
18.000					■	0.750	16.500	138.173
					■	0.938	16.124	170.924
				■	■	1.000	16.000	181.560
					■	1.156	15.688	207.957
					■	1.250	15.500	223.613
					■	1.375	15.250	244.138
				■	■	1.500	15.000	264.330
					■	1.562	14.876	274.221
					■	1.750	14.500	303.713
				■	■	2.000	14.000	341.760
					■	2.250	13.500	378.473
					■	2.500	13.000	413.850
				■	■	3.000	12.000	480.600
				■	3.500	11.000	542.010	
				■	4.000	10.000	598.080	

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
18.500					■	0.750	17.000	142.178
					■	1.000	16.500	186.900
					■	1.250	16.000	230.288
					■	1.500	15.500	272.340
					■	2.000	14.500	352.440
18.625					■	1.375	15.875	253.316
19.000					■	0.750	17.500	146.183
				■	■	1.000	17.000	192.240
					■	1.250	16.500	236.963
				■	■	1.500	16.000	280.350
					■	1.750	15.500	322.403
					■	2.000	15.000	363.120
				■	2.500	14.000	440.550	
				■	3.000	13.000	512.640	
19.500					■	2.750	14.000	491.948
20.000					■	0.750	18.500	154.193
					■	0.812	18.376	166.401
					■	1.000	18.000	202.920
					■	1.031	17.938	208.869
					■	1.250	17.500	250.313
					■	1.281	17.438	256.096
					■	1.500	17.000	296.370
					■	1.750	16.500	341.093
					■	2.000	16.000	384.480
					■	2.250	15.500	426.533
21.000					■	0.750	19.500	162.203
					■	1.000	19.000	213.600
					■	1.250	18.500	263.663
					■	1.500	18.000	312.390
					■	1.750	17.500	359.783
					■	2.000	17.000	405.840
					■	2.500	16.000	493.950
					■	3.000	15.000	576.720
					■	3.500	14.000	654.150
					■	4.000	13.000	726.240
22.000					■	0.750	20.500	170.213
					■	1.000	20.000	224.280
					■	1.250	19.500	277.013
					■	1.500	19.000	328.410
					■	1.750	18.500	378.473
					■	2.000	18.000	427.200
					■	2.500	17.000	520.650
					■	3.000	16.000	608.760
					■	3.500	15.000	691.530
				■	4.000	14.000	768.960	



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
23.000					■	0.750	21.500	178.223
					■	1.000	21.000	234.960
					■	1.500	20.000	344.430
					■	2.000	19.000	448.560
					■	2.500	18.000	547.350
					■	3.000	17.000	640.800
24.000					■	0.688	22.624	171.293
					■	0.750	22.500	186.233
					■	0.969	22.062	238.346
					■	1.000	22.000	245.640
					■	1.219	21.562	296.584
					■	1.250	21.500	303.713
					■	1.531	20.938	367.392
					■	1.750	20.500	415.853
					■	1.812	20.376	429.386
					■	2.000	20.000	469.920
					■	2.062	19.876	483.122
					■	2.344	19.312	542.135
					■	2.500	19.000	574.050
					■	3.000	18.000	672.840
					■	3.500	17.000	766.290
					■	4.000	16.000	854.400
25.000					■	1.000	23.000	256.320
26.000					■	1.000	24.000	267.000
					■	1.500	23.000	392.490
					■	2.000	22.000	512.640
					■	2.500	21.000	627.450
					■	3.000	20.000	736.920
					■	3.500	19.000	841.050
					■	4.000	18.000	939.840

FLUID POWER PRODUCTS

Suitable-to-Hone

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
1.625		■				0.189	1.247	2.899
2.000		■				0.253	1.494	4.720
2.022		■				0.511	1.000	8.246
2.125		■				0.189	1.747	3.908
2.250		■				0.253	1.744	5.396
2.375		■				0.189	1.977	4.412
2.500	■	■				0.252 0.260	1.996 1.982	6.050 6.220
2.625		■				0.189 0.306	2.247 2.013	4.917 7.579
2.750		■				0.252 0.378	2.246 1.994	6.723 9.576
2.774	■					0.512	1.750	12.369
2.875		■				0.191	2.494	5.475
3.000		■				0.252 0.378 0.503	2.496 2.245 1.994	7.396 10.585 13.414
3.125		■				0.316 0.317	2.494 2.491	9.480 9.507
3.250		■				0.253 0.378 0.503	2.745 2.494 2.244	8.098 11.594 14.757
3.375		■				0.190	2.996	6.463
3.500	■	■				0.253 0.254 0.260 0.378 0.503	2.995 2.992 2.980 2.744 2.494	8.774 8.805 8.997 12.604 16.100
3.519	■					0.510	2.499	16.389
3.520		■				0.263	2.995	9.148
3.555		■				0.465	2.625	15.346
3.563		■				0.285	2.994	9.978
3.750		■				0.253 0.254 0.378 0.503	3.245 3.243 2.994 2.744	9.449 9.484 13.613 17.443
3.875		■				0.316	3.244	12.011
4.000	■	■				0.253 0.254 0.260 0.378 0.503	3.495 3.492 3.480 3.244 2.994	10.125 10.162 10.385 14.622 18.786

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
4.250		■				0.253 0.378 0.380 0.504	3.744 3.494 3.491 3.243	10.800 15.631 15.706 20.164
4.331		■				0.201	3.929	8.866
4.375		■				0.192	3.992	8.577
4.500		■				0.253 0.254 0.260 0.378 0.504 0.630	3.994 3.992 3.980 3.744 3.493 3.240	11.476 11.518 11.774 16.641 21.509 26.039
4.520	■					0.385	3.750	17.002
4.625		■				0.316	3.994	14.542
4.750	■	■				0.253 0.378 0.385 0.504	4.244 3.994 3.980 3.743	12.151 17.650 17.948 22.855
4.813		■				0.412	3.990	19.365
5.000	■	■				0.253 0.254 0.260 0.378 0.504 0.505	4.494 4.492 4.480 4.244 3.993 3.991	12.827 12.875 13.162 18.659 24.201 24.243
5.024		■				0.387	4.250	19.165
5.039		■				0.261	4.517	13.319
5.125		■				0.316 0.317	4.494 4.491	16.230 16.278
5.250		■				0.253 0.378 0.504 0.630	4.744 4.494 4.243 3.990	13.502 19.668 25.546 31.085
5.433		■				0.260	4.913	14.364
5.500	■	■				0.253 0.260 0.378 0.504 0.630 0.760	4.994 4.980 4.744 4.493 4.240 3.980	14.178 14.550 20.678 26.892 32.767 38.474
5.625		■				0.316	4.993	17.917
5.674		■				0.340	4.994	19.369



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
5.750		■				0.253	5.244	14.853
		■				0.378	4.994	21.687
		■				0.380	4.991	21.794
		■				0.504	4.743	28.238
6.000	■	■				0.253	5.494	15.529
		■				0.260	5.480	15.939
		■				0.378	5.244	22.696
		■				0.504	4.993	29.583
6.063		■				0.412	5.240	24.865
6.250		■				0.378	5.494	23.705
		■				0.380	5.491	23.823
		■				0.504	5.242	30.929
		■				0.630	4.991	37.814
6.500		■				0.254	5.993	16.944
		■				0.255	5.991	17.008
		■				0.378	5.744	24.715
		■				0.504	5.492	32.275
		■				0.630	5.241	39.496
				■		0.766	4.968	46.909
6.625		■				0.316	5.993	21.292
6.750		■				0.378	5.994	25.724
		■				0.380	5.991	25.852
		■				0.504	5.742	33.620
		■				0.630	5.491	41.178
6.780		■				0.266	6.248	18.505
7.000		■				0.253	6.494	18.231
		■				0.378	6.244	26.733
		■				0.504	5.992	34.966
		■				0.505	5.990	35.030
7.041		■				0.500	6.041	34.929
7.250		■				0.378	6.494	27.743
		■				0.504	6.243	36.312
		■				0.513	6.224	36.911
		■				0.629	5.992	44.478
7.500		■				0.253	6.994	19.582
		■				0.378	6.744	28.752
		■				0.505	6.491	37.727
		■				0.630	6.240	46.224
				■		0.767	5.966	55.154
7.625		■				0.566	6.493	42.671
7.750		■				0.378	6.994	29.761
		■				0.631	6.489	47.976
8.000		■				0.253	7.494	20.933
		■				0.378	7.244	30.770
		■				0.504	6.993	40.349
		■				0.505	6.990	40.424
				■		0.768	6.464	59.319
				■		1.017	5.966	75.846

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
8.250		■				0.378	7.494	31.780
		■				0.504	7.243	41.695
		■				0.629	6.992	51.196
8.500		■				0.255	7.990	22.454
		■				0.504	7.493	43.040
				■		0.768	6.964	63.420
				■		1.018	6.464	81.346
8.750		■				0.379	7.993	33.883
		■				0.629	7.492	54.555
9.000		■				0.379	8.242	34.895
		■				0.504	7.993	45.732
		■				0.509	7.982	46.158
				■		0.771	7.458	67.760
				■		1.018	6.964	86.782
9.250		■				0.629	7.992	57.913
9.500		■				0.504	8.492	48.423
		■				0.556	8.388	53.110
				■		0.771	7.958	71.877
				■		0.834	7.832	77.189
				■		0.905	7.690	83.074
				■		1.023	7.454	92.617
9.750		■				0.630	7.740	61.363
10.000		■				0.504	8.992	51.114
				■		0.773	8.454	76.175
				■		1.021	7.958	97.910
10.250		■				0.505	9.240	52.559
		■				0.629	8.992	64.631
		■				0.631	8.988	64.823
10.500		■				0.505	9.490	53.907
				■		0.773	8.954	80.303
10.750	■					0.594	9.562	64.429
10.804		■				0.477	9.850	52.609
10.938	■					0.594	9.750	65.622
11.000		■				0.517	9.966	57.883
				■		0.774	9.453	84.531
				■		1.023	8.954	109.005
11.500				■		0.778	9.944	89.090
11.750				■		0.903	9.944	104.609
12.000		■				0.517	10.966	63.404
				■		0.778	10.444	93.244
				■		1.028	9.944	120.462
14.000				■		1.035	11.930	143.313

Honed Tubing

ID Honed to 16 Max RA

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot	Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
1.625		H				0.186	1.250/1.253	2.859	3.375		H				0.186	3.000/3.003	6.335
1.750		H				0.124	1.500/1.503	2.153	3.500		H				0.250	2.997/3.000	8.678
1.875		H				0.186	1.500/1.503	3.355			H				0.249	3.000/3.003	8.645
2.000		H				0.124	1.750/1.753	2.484			H				0.374	2.750/2.753	12.486
2.125		H				0.186	1.750/1.753	3.852			H				0.499	2.500/2.503	15.993
2.250		H				0.124	2.000/2.003	2.816	3.520		H				0.259	3.000/3.003	9.020
		H				0.249	1.750/1.753	5.321			H				0.280	3.000/3.003	9.817
2.375		H				0.186	2.000/2.003	4.348	3.563		H				0.282	2.997/3.000	9.882
		H				0.188	1.997/2.000	4.391			H				0.249	3.250/3.253	9.310
2.500		H				0.124	2.250/2.253	3.147			H				0.250	3.247/3.250	9.345
		H				0.249	2.000/2.003	5.986			H				0.374	3.000/3.003	13.485
2.625		H				0.186	2.250/2.253	4.845	3.750		H				0.499	2.750/2.753	17.326
		H				0.302	2.018/2.021	7.493			H				0.311	3.250/3.253	11.838
2.750		H				0.124	2.500/2.503	3.478	4.000		H				0.250	3.497/3.500	10.013
		H				0.249	2.250/2.253	6.651			H				0.249	3.500/3.503	9.975
		H				0.374	2.000/2.003	9.491			H				0.374	3.250/3.253	14.483
2.875		H				0.188	2.497/2.500	5.395	4.125		H				0.311	3.500/3.503	12.668
		H				0.186	2.500/2.503	5.342			H				0.249	3.750/3.753	10.640
3.000		H				0.124	2.750/2.753	3.809	4.250		H				0.374	3.500/3.503	15.482
		H				0.249	2.500/2.503	7.316			H				0.499	3.250/3.253	19.990
		H				0.374	2.250/2.253	10.489	4.375		H				0.186	4.000/4.003	8.321
	H					0.423	2.151/1.154	11.642			H				0.249	4.000/4.003	11.305
	H					0.499	2.000/2.003	13.329	4.500		H				0.374	3.750/3.753	16.481
	H					0.522	1.954/1.957	13.815			H				0.499	3.500/3.503	21.323
3.125		H				0.311	2.500/2.503	9.347	4.625		H				0.311	4.000/4.003	14.329
		H				0.313	2.497/2.500	9.400			H				0.249	4.250/4.253	11.970
3.250		H				0.124	3.000/3.003	4.140	4.750		H				0.374	4.000/4.003	17.479
		H				0.249	2.750/2.753	7.981			H				0.499	3.750/3.753	22.655
		H				0.374	2.500/2.503	11.488	4.813		H				0.407	3.997/4.000	19.152
		H				0.499	2.250/2.253	14.661			H				0.249	4.500/4.503	12.634
		H							5.000		H				0.374	4.250/4.253	18.478
		H									H				0.375	4.247/4.250	18.523
		H									H				0.499	4.000/4.003	23.987



Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
5.125		H				0.311	4.500/4.503	15.990
5.250		H				0.249	4.750/4.753	13.299
		H				0.374	4.500/4.503	19.476
		H				0.499	4.250/4.253	25.320
		H				0.624	4.000/4.003	30.829
5.500		H				0.249	5.000/5.003	13.964
		H				0.374	4.750/4.753	20.475
		H				0.499	4.500/4.503	26.652
5.625		H				0.311	5.000/5.003	17.650
5.674		H				0.336	5.000/5.003	19.155
5.750		H				0.249	5.250/5.253	14.629
		H				0.374	5.000/5.003	21.473
		H				0.375	4.997/5.000	21.527
		H				0.499	4.750/4.753	27.984
6.000		H				0.249	5.500/5.503	15.294
		H				0.374	5.250/5.253	22.472
		H				0.375	5.247/5.250	22.528
		H				0.499	5.000/5.003	29.317
6.063		H				0.406	5.247/5.251	24.529
6.250		H				0.374	5.500/5.503	23.471
		H				0.375	5.497/5.500	23.529
		H				0.499	5.250/5.253	30.649
		H				0.624	5.000/5.003	37.493
6.500		H				0.249	6.000/6.003	16.623
		H				0.250	5.997/6.000	16.688
		H				0.374	5.750/5.753	24.469
		H				0.499	5.500/5.503	31.981
		H				0.624	5.250/5.253	39.160
6.625		H				0.311	6.000/6.003	20.972
6.750		H				0.374	6.000/6.003	25.468
		H				0.499	5.750/5.753	33.314
		H				0.624	5.500/5.503	40.826
7.000		H				0.249	6.500/6.503	17.953
		H				0.374	6.250/6.253	26.466
		H				0.499	6.000/6.003	34.646
		H				0.500	5.997/6.000	34.710

Outside Diameter Inches	DOM	ST52	CDS	ALY	HFS	Wall Thickness Inches	Inside Diameter Inches	Weight per Foot
7.250		H				0.374	6.500/6.503	27.465
		H				0.499	6.250/6.253	35.978
		H				0.624	6.000/6.003	44.158
7.500		H				0.248	7.000/7.004	19.208
		H				0.373	6.750/6.754	28.391
		H				0.498	6.500/6.504	37.241
		H				0.500	6.497/6.501	37.380
7.750		H				0.373	7.000/7.004	29.387
		H				0.623	6.500/6.504	47.420
8.000		H				0.248	7.500/7.504	20.532
		H				0.373	7.250/7.254	30.383
		H				0.498	7.000/7.004	39.900
8.250		H				0.373	7.500/7.504	31.379
		H				0.498	7.250/7.254	41.230
		H				0.623	7.000/7.004	50.747
8.500		H				0.248	8.000/8.004	21.857
		H				0.498	7.500/7.504	42.560
8.750		H				0.373	8.000/8.004	33.371
		H				0.623	7.500/7.504	54.074
9.000		H				0.373	8.250/8.254	34.367
		H				0.498	8.000/8.004	45.219
9.250		H				0.623	8.000/8.004	57.401
9.500		H				0.498	8.500/8.505	47.878
		H				0.548	8.400/8.405	52.393
9.750		H				0.623	8.500/8.505	60.728
10.000		H				0.498	9.000/9.005	50.538
10.250		H				0.498	9.250/9.255	51.867
		H				0.623	9.000/9.005	64.055
10.500		H				0.498	9.500/9.505	53.197
11.000		H				0.498	10/10.005	55.856
11.750			H			0.875	10/10.005	101.627
12.000			H			1.000	10/10.005	117.480

Chrome Plated Piston Rod Stock

Outside Diameter Inches	Weight per Foot	Chrome Plated						Induction Hardened Chrome Plated					
		50K Min Yld	75K Min Yld		100K Min Yld			50K Min Yld	75K Min Yld		100K Min Yld		
		.001"	.0005"	.001"	.002"	Chrome Thickness			.001"	.0005"	.001"	.0005"	.001"
				.0005"	.001"	.002"							
0.500	0.67					●	●						
0.625	1.04					●	●					●	●
0.750	1.50					●	●					●	●
0.875	2.05					●	●						
1.000	2.67		●	●		●	●	●				●	●
1.125	3.38		●	●		●	●					●	●
1.250	4.18		●	●		●	●	●				●	●
1.375	5.05		●	●		●	●	●				●	●
1.500	6.01		●	●		●	●	●				●	●
1.625	7.06					●	●						
1.750	8.19		●	●		●	●	●				●	●
1.875	9.40					●	●						
2.000	10.69		●	●	●	●	●	●				●	●
2.125	12.07					●	●	●				●	●
2.250	13.53		●	●		●	●	●				●	●
2.375	15.08					●	●						
2.500	16.71		●	●	●	●	●	●				●	●
2.750	20.21		●	●	●	●	●	●				●	●
3.000	24.06		●	●	●	●	●	●				●	●
3.250	28.23		●	●	●	●	●	●				●	●
3.500	32.74		●	●	●	●	●	●				●	●
3.750	37.59		●	●	●	●	●	●				●	●
4.000	42.77		●	●	●	●	●	●				●	●
4.250	48.28		●	●	●	●	●	●				●	●
4.500	54.13		●	●	●	●	●	●		●	●	●	●
4.750	60.31		●	●	●					●	●		
5.000	66.82		●	●	●					●	●		
5.250	73.67	●	●	●					●	●	●		



Outside Diameter Inches	Weight per Foot	Chrome Plated						Induction Hardened Chrome Plated					
		50K Min Yld		75K Min Yld		100K Min Yld		50K Min Yld		75K Min Yld		100K Min Yld	
		Chrome Thickness											
		.001"	.0005"	.001"	.002"	.0005"	.001"	.002"	.001"	.0005"	.001"	.0005"	.001"
5.500	80.77	●	●	●	●				●	●	●		
5.750	88.28	●	●	●	●				●	●	●		
6.000	96.12	●	●	●	●				●	●	●		
6.500	112.80	●							●				
7.000	130.80	●							●				
7.500	150.20	●							●				
8.000	170.88	●							●				
8.500	192.90	●							●				
9.000	216.27	●											
10.000	267.00	●							●				
12.000	384.50	●							●				

Outside Diameter Inches	Weight per Foot	Chrome Plated						Induction Hardened Chrome Plated					
		50K Min Yld	75K Min Yld		100K Min Yld			50K Min Yld	75K Min Yld		100K Min Yld		
		.001"	.0005"	.001"	.002"	Chrome Thickness			.001"	.0005"	.001"	.0005"	.001"
				.0005"	.001"	.002"							
20MM	1.66						●						●
25MM	2.59		●	●			●						●
28MM	3.25						●						●
30MM	3.73		●	●			●				●		●
32MM	4.24						●						●
35MM	5.08		●	●			●						●
36MM	5.37						●						●
40MM	6.63		●	●			●						●
42MM	7.31						●						●
45MM	8.39		●	●			●						●
50MM	10.36		●	●			●						●
55MM	12.53		●	●			●						●
56MM	12.99						●						●
60MM	14.91		●	●			●				●		●
63MM	16.44						●						●
65MM	17.50		●	●			●				●		●
70MM	20.30		●	●			●						●
75MM	23.30		●	●			●						●
80MM	26.52		●	●			●						●
85MM	29.93		●	●			●						●
90MM	33.56		●	●			●						●
95MM	37.39		●	●			●						●
100MM	41.43		●	●			●						●



Outside Diameter Inches	Weight per Foot	Chrome Plated						Induction Hardened Chrome Plated					
		50K Min Yld		75K Min Yld		100K Min Yld		50K Min Yld	75K Min Yld		100K Min Yld		
		Chrome Thickness											
		.001"	.0005"	.001"	.002"	.0005"	.001"	.002"	.001"	.0005"	.001"	.0005"	.001"
105MM	45.68		●	●			●						●
110MM	50.13		●	●			●						●
115MM	54.79		●	●			●				●		●
120MM	59.66		●	●							●		
125MM	64.73		●	●							●		
130MM	69.94	●	●	●					●		●		
140MM	81.12	●	●	●					●		●		
150MM	93.13	●	●	●					●		●		
160MM	105.94	●							●				
170MM	119.60	●							●				
180MM	134.10	●							●				
190MM	149.38	●							●				
200MM	165.54	●							●				